

Sides



- sc
- x ssc
- | fpdc
- pattern rep

Rnd 1: Ch 1 and turn, sc in each of 43 sc across, ch 1 for corner, with same side still facing, rotate piece and work 17 sc evenly spaced along side edge, ch 1 for corner, with same side still facing, rotate piece and working into bottom of beg foundation ch, sc in each of 43 ch, ch 1 for corner, with same side still facing, rotate piece and work 17 sc evenly spaced along other side edge, ch 1 for corner, join with sl st to first sc—120 sc plus 4 ch-1 corner spaces.

Rnd 2: Ch 2 and turn (does not count as a st), dc in each sc around and in each ch-1 space at corners, join with sl st to top of beg ch-2—124 dc.

Rnd 3 (RS): Ch 1 and turn, bpsc in each st around, join with sl st to first sc—124 bpsc.

Rnd 4 and all even rnds or WS rnds: Ch 1 and turn, sc in each st around, join with sl st to first sc.

Rnd 5: Ch 1 and turn, sc in each of next 43 sc across, fpdc around the post of next sc 2 rows below, sk the sc behind this fpdc, sc in each of next 17 sc, fpdc around the post of next sc 2 rows below, sk the sc behind this fpdc, sc in each of 43 ch, fpdc around the post of next sc 2 rows below, sk the sc behind this fpdc, sc in each of next 17 sc fpdc around the post of next sc 2 rows below, sk the sc behind this fpdc, join with sl st to first sc—124 sts including 4 fpdc at corners.

